

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
4 January 2001 (04.01.2001)

PCT

(10) International Publication Number
WO 01/01593 A1

(51) International Patent Classification⁷: **H04B 1/707**

Eindhoven (NL). VAN DRIEL, Carel, J., L. [NL/NL];
Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).

(21) International Application Number: PCT/EP00/05906

(22) International Filing Date: 26 June 2000 (26.06.2000)

(74) Agent: GROENENDAAL, Antonius, W., M.; Internationaal Octrooibureau B.V., Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).

(25) Filing Language:

English

(81) Designated States (*national*): JP, US.

(26) Publication Language:

English

(84) Designated States (*regional*): European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).

(30) Priority Data:

99202096.6

29 June 1999 (29.06.1999) EP

Published:

— With international search report.

— Before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments.


(71) Applicant (*for all designated States except US*): KONINKLIJKE PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).

(72) Inventors; and

(75) Inventors/Applicants (*for US only*): VAN HOUTUM, Wilhelmus, J. [NL/NL]; Prof. Holstlaan 6, NL-5656 AA

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: SYNCHRONISATION CODEWORD FOR INTERFERENCE REDUCTION IN A CDMA SYSTEM



(57) Abstract: The CDMA communication system according to the invention comprises at least one primary station (2) and a plurality of secondary stations (4). The primary station (2) and the secondary stations (4) can exchange CDMA signals (18) via a communication medium (6). The secondary stations (4) each comprise a modulator (10) for modulating data signals (16) with code words (14) in order to obtain the CDMA signals (18). A modulator (10) of a secondary station (4) initially modulates its data signal (16) with an initial code word until that secondary station (4) is synchronised with the primary station (2). From that moment on the data signal (16) is modulated with a final code word. Ideally, an initial code word is used which is, for every possible time shift of that code, substantially orthogonal to all the final code words in use by the already synchronised secondary stations (4). Such an initial code word does not interfere with the CDMA signals (18) received and transmitted by the already synchronised secondary stations (4) and is therefore very well suited for the purpose of synchronising a secondary station (4) with the primary station (2). If Walsh-Hadamard codes are used as code words the code word corresponding to the first row of the Walsh-Hadamard matrix is an example of such an ideal initial code word.

WO 01/01593 A1